

DF1800 Catalogue

Local Data Monitoring System



For Reliable, Secure and Economical Energy System Operation

Dongfang Electronics International Engineering Co., Ltd. Dongfang Electronics Co., Ltd.




Summary

DF1800 Local Data Monitoring System is integrated solution for analysis and operation of transmission and distribution substation, photovoltaic power station and wind power station. DF1800 provides the functions of supervisory & control, network analysis, safe and economical operation instruction, dispatch information management, active power/reactive power control, voltage control, etc.

DF1800 is developed under an established quality assurance program and has been used as high reliability Electrical Power Automation Systems software worldwide.

DF1800 was developed under a modular designing concept and with Server/Client architecture. It is a Reliable, Scalable and Flexible system.

System Hierarchy



DF1800 LDMS software system has four layers in design:

The First: Distributed System Operation and Development Middleware Platform

It is called general OS platform layer. It is a middleware between DF1800 LDMS system and different operating systems. This middleware isolates DF1800 applications with OS, at the same time, it provides uniformed OS function interface for DF1800 applications, and it provides operation environment for the applications. And it makes DF1800 system high portable. It assures that different operation systems like Windows, different UNIX, Linux can be used at the same time in system. For example HP-UNIX, IBM AIX, SUN Solaris,

Linux, Windows Server & Windows Workstation, etc. So it can provide most cost-effective solutions for power enterprises and protect the customer's investment.

The Second: Object Oriented Real Time Database Middleware Layer following IEC61970/IEC61968

It is called uniform power application platform. It adopts the object oriented power device model definition and EMSAPI established by IEC, it is a power system application oriented real time database management system. The

ODLE

DF1800 Local Data Monitoring System Catalogue

special platform, makes SCADA, AVC, AGC have application level openness based on IEC 61970/61968 CIM/CIS, and makes the application software modules "Plug and Play" possible.

The Third: Application Platform Layer

It provides general application interfaces and service for SCADA, AGC, AVC and other applications. It is composed of integrated GUI, integrated drawing-modeldatabase editing tool, printing service, data acquisition service, web service and interconnection adapter with other systems. The establishment of application platform layer makes it easy for the system development and upgrade.

The Fourth: Power Application Software Layer

This layer includes many power system applications, such as SCADA, AGC, AVC, Photovoltaic Power Forecasting, Wind Power Forecasting, etc.


Application Modules

DF1800 SCADA Software Modules

DF1800 SCADA HMI DF1800 SCADA Database Editor DF1800 SCADA Data Viewer DF1800 SCADA Database Backup Manager DF1800 SCADA Database Connection Monitor DF1800 SCADA Drawing Editor DF1800 SCADA Drawing Editor DF1800 SCADA Front End Viewer DF1800 SCADA Front End Server DF1800 SCADA Real Time Alarm Viewer DF1800 SCADA Report Manager DF1800 SCADA Report Manager DF1800 SCADA Real Time Database Sever DF1800 SCADA Real Time Database Viewer

DF1800 Advanced Software Modules

DF1800 Web Server DF1800 Application Programming Interface DF1800 Photovoltaic/Wind Power Forecasting DF1800 Automatic Generation Control DF1800 Automatic Voltage Control





System Features

Integrated Hardware/Software Platform

• Provide uniform application developing interfaces to improve the efficiency of system upgrade and customer development

• Provide Uniform, extensible, distributed, transparent operating system platform

• Flexible configuration and expansion ability

• Support Unix OS, Windows series OS and Linux OS

• Support commercial relation database such as Oracle, Sybase, SQL-server and MySQL

• Standard external communication interface to integrate with other systems

Features of SCADA Package

• Secured operation via Area of Responsibility and password verification

• Secured data viewing on displays and alarm processing based on AOR

• Perfect data processing and calculations functions, such as engineering unit conversion, multi-level limits checking, and rate of change checking etc

• Advanced alarm and event processing functions

• Support alarm information forwarding via mobile short message system

Control Permissive interlocks logical definition interface

• Support continuous SCADA snapshots for archiving or PDR

• Support dual net, dual-computer redundancy

• Support Server/Client Topology Model, and support remote operation workstation accessing SCADA function

• Provide programming language for

customized function developing

Friendly Human Machine Interface

• Built-in intelligent graphics

- Display Real-time data on one-line diagrams
- Configurable font types, styles & colors
- Configurable display ratings & modes

• Graphical display of equipment impedance & grounding

• Automatic distinguish of energized & deenergized elements

• Text box editor with dynamic link to properties

- Intelligent text box & hyperlink marks
- User-friendly plotting

CIM based diagram-model-database integration

• CIM based graphic primitive and modeling

• Diagram drawing, model building, and data editing integrated

Plot-browse-test integration

• Transmission/distribution network modeling integration

Customizable HMI

• Use advanced QT developing platform, provide identical HMI style under different OS

• Support user customized device primitive and menu

• Provide Unitizing Summaries Displays

• Support X-Window and OSF/Motif and three-dimensional graphics Based on OpenGL

• Support various drawing format such as Bitmap, DXF and gif images etc


• Support automatic diagram generation, including diagram of total network power flow, diagram of power supply tracing, diagram of bay, etc



Basic SCADA Modules

DF1800 SCADA HMI

DF1800 SCADA HMI Module is distributed and fully-graphical human-machine interface developed based on network window system X-Window, industrial standard OSF/Motif or Windows and threedimensional graphics standard OpenGL. The system fully takes into account the requirements different proposed by different applications, such as NAS, DMS, AGC, DMIS, AMR and TMS when designing, and mixes the miscellaneous requirements. All the operations can be performed on the human-machine interface, via clicking mouse to make the operation more convenient. The shortcut operations are defined too, which make the operation more simple and convenient. The single key can be defined to navigate display also to speed up the operation.



DF1800 SCADA Database Editor

• Set an object-oriented data model referenced to CIM, to establish the foundation for the "plug-and-play" of the application software.

• Implementing the "seamless connection" between commercial relational database and real-time database.

• Fulfill real-time database management of distributed application environment to realize the independence and transparence of physical storage.


• Implement the fast copy and backup of database.

ile Edit Check Help					
🖬 🙂 🔒 🖴 🔟 🔚 ·	-	D 🗈 🗙 🛛	O CIMS		
AppSel SCADA AppClassTab	le	- EditStyle	F EdifWholeTable C EditTable	Block C EditSi	ngleRecord
Code •	-	Match Whole V	Vord Only		
SCADA_AppClassTeble[Dbl.*		Code	Description	DescLocking	SecurityGrade.
BaseVoltageTable	1	Bbg10kV5V	BeiGouBbg10kV5BusVolt	0	0
BreakerConnSwitchTo	2	Bbg110kV4V0	BeiGou110kV4#BusUo	0	0
BreakerProtModReITz	3	Bbg110KV5V0	BeiGouBbg110kV5BusUo	0	0
	4 Kbg215P		BeiGouKbg215CommonBreekP	0	0
BreakerProtRelTable	5	Kbg312Q	BeiDengLineKbg312CommonBre	0	0
- BreakerReplaceRelTe	6	Kbg313Q	BeiXuLineKbg313CommonBreak	0	0
CalcExpressionTable	7	Kbg3140	BeiGouKbg314CommonBreekQ	0	0
CalculatedVariableTat	0	Kbg315Cs	BeiGouKbg315CommonBreakPF	0	0
	9	Kbg315Q	BeiGouKbg315CommonBreakO	0	0
- ChannelParaTable	10	Kbg3210	WeiNiLineKbg321CommonBreak	0	0
- CommunicationGroupT	11	Kbg322Cs	BeiGouKbg322CommonBreekPf	0	0
CommunicationParaTe	12	Kbg3220	BeiGouKbg322CommonBreekO	0	0
DA_AreaParaTable	13	Kbg323la	BoHaiKbg323CommonBreakta	0	0
- DA_BreakerTpTable	14	Kbg323lb	BoHeiKbg323CommonBreeklb	0	0
	15	Kbg3230	BoHeiKbg323CommonBreekQ	0	0
- DA_CBreakParaTbl	16	Tbg1#HDw	BeiGou1#zbHighVoltDW	0	0
DA_LineTpTable	11	This 94404	RainauTha2#Hisk\AaFAU	0	0

DF1800 SCADA Database Viewer


DF1800 SCADA Database Viewer Module is responsible for the query or modification of historical data. The system provides a database interface to display data at any time interval in tables or curves. The historical data can be modified with proper authority, and the system will re-calculate the modified data and make statistics again.






DF1800 SCADA Database Backup Manager

DF1800 SCADA Database Backup Manager module is for dumping, replication and transcription the Database, its menu is convenient and friendly. To display the parameter table structure is also provided.



DF1800 SCADA Database Connection Monitor


DF1800 SCADA Database Connection Monitor Module is the interface for outputting database accessing command and the operation result. This interface helps the system administrator to diagnose the system running status.



DF1800 SCADA Drawing Editor

DF1800 SCADA Drawing Editor Module adopts the object-oriented technique. All devices and electric power symbol are treated as objects. The system can display three dimension images and flashes, many kinds of fonts. The system also supports Unix system X terminal and simulated X terminal on a PC.

DF1800 SCADA Drawing Editor Module is able to display drawing on static or dynamic mode with multilayer structure. The system has unlimited display of layer and view and may set database information for Power Device. The system also integrates the power device symbol pre-defined function. The DF1800 SCADA Drawing Editor can synchronize the modified drawing via network after the archiving command is issued.



DF1800 SCADA Front End Viewer

DF1800 SCADA Front End Viewer Module displays the parameters of the FEP system, checks the channel buffer, monitors the RTU status, watches the raw real-time data, and tests the data transmission. It also acts as the protocol analyzer.



 Control water
 Control

DF1800 SCADA Front End Sever

• Support synchronous/asynchronous channel

• Auto-Switch main/standby channel according to channel status

• Auto-Switch main/standby FEP according to host status

• Monitor and control the running status of channel

• Support all standard international communication protocol (such as IEC60870-5-101, IEC60870-5-103, IEC60870-5-104, IEC61850, MODBUS serial or Over IP, DNP 3.0 serial or Over IP, etc.)

• Adopt Terminal Server to allow the serial equipment to be connected to LAN and WAN directly.


Support 4G/3G/GPRS communication

DF1800 SCADA Real Time Alarm Viewer

All the alarm and event have attributes like: priority, point or device name, substation name, type, time, status or value, area of responsibility, etc. And alarm style, description, sound or not are user definable.

Alarms include: fault trip, no command change of switch, protection signal, fault trip times of breaker violating limit, analog value violating limits, change rate of analog point violating limit, and so on.

DF1800 SCADA Real Time Alarm Viewer provides SMS and Email Messenger. The module uses the short-message service supplied by the mobile communication service to send the classified and filtered SCADA system's information to the dedicated mobile phone. The subsystem can make the user gathering the real-time information of the power grid easily at any time and in any place via using the public SMS. It can speed up the efficiency for restoring the power grid's abnormal accident. Customer can set the information style according to their requirement. The improve the system can operation efficiency and reduce the labor intension for the operator.



DF1800 SCADA Historical Event Viewer

DF1800 SCADA Historical Event Viewer Module is the interface to retrieve the history event. It is useful to analyze accident of the power grid. The interface provides the access to set the event searching condition.

The module provides the function of event editing, such as add an event record, delete an event record or modify an event record.




		-			and the second second					
N NTU		18	Enline	Evention	Eventine.	Eventime	Scopforeit	Methefiane	Decide	
		52	0050	operation event	LoadSalabare	2007-10-34 14 45 15 259	ater	Marel	Load Sable	anal
Date			0051	specifics arrest	Load status	2007-10-24 14:45 15:575	achin.	Mart	Load table -	**
Minere: 16/24/2807 20 12:00:00 AM	-	53	0052			2007/10/24 14:45 15:571	abin	West	Load table	
TILGACIER BILGACK TIPM	4	- 54	0013			2007-10-34 14 45 13 545	abin	Marv1	Loadtable	-
and I second a Till owned and	-	55	0.54	specifics avent	LouD statuse	2007-10-24 14 45 13:562	athin	MarkE	Load table	-
RTU			9355			2007/10/24 14:45 13:579		Mark	Loadiable	**
Select (d. Bevera		17	0056	specifics arrest	LosDatase	2007/10/24 14 47:33 734	abin	Mart	Load table 1	lass:
			0357			2007/10/24 14:47 25:525		Marel	Load189e	left-
Natural Code	•	153	8750	operation event	LonDatabase	2007/10/24 14:47 40:156	abir	Munt	Load table p	pol.
AnD 0 PelaDan al		62	0059	specializes a rend	LonD status	2007-10-24 14 47 40 312	484	Marit	Load table	-
Debberten de	-	\$2.	0068	operation arrest	Load statute	200710-2414.47.40.343	abin.	Mark.	Loud table	pile
BellowDon bo		62	0067	speaks aveil	LosDatabase	2007-10-24 14:47,40:437	where .	Mark	Load table ;	100
Duefaber a	-	60	0062	operation event	LonDutation	2007/10/04 14:47:40 500	abe	Marid	Load table ;	Apr .
Despherican da Universitation da		64	0063	operation arrent	LonDetates	2007/10/24 14:47:42/545	abir.	West	Load table	Abi 1
Duritizhan ev		15	0064	operation arrent	LoadDatates	2007/10/24 14 40:00 705	abe	Marit	Load table 1	dres 1
Distant a		66	0065	operation events	Load states	2007/10/24 14:48:00.075	athin	Mart	Load table :	and i
T YizhongDan ye		67	0066	operation event	Loadistate	2007-10-24 14 48:03 210	athin	Marvt	Load table :	-
		68	0067	specifics event	LiveD at all area	2007/15/24 14 48:09/212	abie	Maryl	Load table	64.
194 ·		65	3068	operation event	LonDelahare	2007-10-24 14 48 09 326	ater	Marvit	Load table :	ote
Salest (d. Bernetin			0069	spendion event	LostD stabare	2007-10-24 14 48:09 421	admin	Manif	Load table	par.
Digital all event	•	71	0075	operation event	LonDatabase	2007-10-24 14 40:03 454	adran.	Mart	Load table ;	AP.
		72	0071	operation event	LowDatabase	2007-10-24 14 48 09 531	alter.	Mart	Load table :	44
20 IC 20 Carloner 20 Faceloner 20 Faceloner 20 Tavioren 20 Tavior		73	0072	operation event	Edifferentiable	2007/10/24 14:09/21 000	Mont	bod :	Mudly D8 p	-
		74	0073	operation meet	5.6Pus?able	2007-10-34 14 12 55 000	Next	Just .	Hody D0 p	-
		75	0074	operation event	EdiPusTable	2007/10/24 14 15 10:000	Merel	100	Modey DR p	-
		78	0075	specifics arrest	£4PasTate	200710-3414-2510-000	News	out .	Mudly DE p	-
		77	0076	speudon event	Edfor/ab	2007-10-24 14:32 49:000	MarvE	(and)	Mudly D0 a	-
		10	0077	(genetion avenue)	ets?ee'tdle	2007-10-34 14 32 05 000	More1	and .	Modky DB p	-
tele .			0078	speakon a-ard	Edificulation	2007/10/24 14:33/57:000	HPupol.	od	Mudly DR p	**
		00	0079	spection event	Eddfaul alle	2007-10-24 14 24 07 000	Nerv1	0.0	Mudly 28 p	
by Oberch		85	0080	specifics event		2007-10-24 14 35 16 000	New1	and .	Mudip-Dill p	
TOE		(i)	1011							1



DF1800 SCADA Report Manager

• Based on MS Excel; Access all the function provided by the MS Excel

- Customized reports generation & plots
- Access the History database by ODBC driver
- Public the Report sheet to Web




DF1800 SCADA System Manager

• Provides system performance output Interfaces according to the OS system management functions

- Provide network communication management
- · Provide distributed objects management
- Provide node and process management


• Provide system on-line diagnose interface



DF1800 SCADA Real Time Database Viewer

DF1800 SCADA Real Time Database

Viewer Module is the interface to display real time database parameter. The interface provides access to view and modify the parameter and help the system administrator to diagnose the consistency between real-time database and relational database.



DF1800 SCADA Real Time Database Sever

DF1800 SCADA Real Time Database Sever adopts Server/Client mode. There is only one node whose database is taken as the referenced one in the whole system, the other nodes copy the referenced one as their local real-time database. The copies of real-time database is updated automatically and kept the same with the referenced one, to meet the data consistency requirement of the distributed

system. Distributed real-time database management solves the problem of maintaining the consistency of real-time

database in the platform level, and carries perfect full-scale management. It makes that the upper applications can process interior data centrally, efficiently balances the system load, and improves the usability and stability of the system.



Advanced Software Modules

DF1800 Web Server

Based on Browser/Server (B/S) architecture

• Provide graphical data browsing via IE browser

• Provide scalable vector graphics and OpenGL displaying style at IE browser

• The real-time data can be updated on the IE browser

• Browsing various reports via IE browser

• Querying the power device parameters via IE browser

• Accesses history data and events via IE browser

DF1800 Application Programming Interface

- · Support constant and variable define
- Support following kinds of calculations
- Arithmetical calculation such as +, -, *, /.
- Relation calculation such as >, <, ==, etc.

• Logic calculation such as AND, OR, NOT, XOR etc.

- Bit operation such as &, | etc.
- Support following kinds of functions

• Mathematic function such as square, square root, mod etc.

• Statistics function such as maximum, minimum and average.

• Bit operation function such as shift left, shift right, rotate shift left, rotate shift right, bit set.

- Trigonometric function such like cos, sin.
- Time function
- Logic function
- Permit function
- User defined function.
- Support sentences of evaluate, return etc.
- Support commands such as remote control, manual data setting

DF1800 Automatic Generation Control

- Collect telemetry for all the required quantities
- Filter telemetry
- Select best alternative telemetry where
- redundant values are available
- Accept scheduled interchange
- Compute the Area Control Error (ACE)
- Filter ACE
- Calculate control allocation
- Issue controls to generators or invertors
- Model and monitor generator or invertors
 response
- Adjust the active power based on the plan curve
- Monitor NERC performance
- Provide the data interface to electricity market
- Adopting the Object-Oriented Structure
 Design

DF1800 Automatic Voltage Control

• Monitor and analyze reactive power and bus voltage to minimize loss by adjusting capacitor and tap ratio of transformers and other reactive power devices

• Constraint reactive power and voltage limits to access to optimal area for power balancing

• Adjust the reactive power based on the plan curve

DF1800 Photovoltaic/Wind Power Forecasting

• Support super short-term forecasting, short-term forecasting, medium- and long-term forecasting

- Support different forecasting algorithm
- Support similar day model

Dongfang Electronics International Engineering Co., Ltd.

Dongfang Electronics Co., Ltd.

Address: No.2 Jichang Road, Yantai, Shandong Province, P.R. China, 264000

Tel: +86-535-5520949

Fax: +86-535-5520930

Email: idf@dongfang-china.com

Website: http://www.dongfang-china.com/en



THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF DONGFANG ELECTRONICS INTERNATIONAL ENGINEERING CO., LTD. ALL RIGHTS RESERVED.